

COAXIAL CONNECTOR, BMA, 50 Ohm, Straight bulkhead cable plug (male)

14_BMA-50-2-33/133_N

Properties

- Offers a range of floating configurations
- High reliability and ease of assembly
- Intermatable with the OSP connectors series
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
BMA	plug	BMA Economic (mech. compatible with BMA Std acc. to Mil)

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	EPDM (Ethylene propylene diene rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	12.4 GHz

Mechanical data	
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	soldered

Environmental data	
Operation temperature	-40 °C ... 125°C

COAXIAL CONNECTOR, BMA, 50 Ohm, Straight bulkhead cable plug (male)

14_BMA-50-2-33/133_N

Ordering Information Table		
Item number	Item description	Packaging type
85006671	14_BMA-50-2-33/133_NH	Bulk 100 pcs

Suitable cables	
Cable group	Y3 - 2 mm / 50 Ohm
	Y16 - 2 mm / 50 Ohm
	Y11 - 2 mm / 50 Ohm
Suitable cables	SR_86_TP_M17
	MULTIFLEX_86
	SUCOFORM_86

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3195 / Date of publication: 25.11.2023 / uncontrolled copy