

Coaxial Cable SPUMA_600

Description

PE Foam - 50 Ohm - double screened



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Aluminium / Copper	Wire	4.44 mm
Dielectric	SPE (Foamed Polyethylene)		11.56 mm
Outer conductor	Aluminum / PES	longitudinal Foil, 100%	11.71 mm
Outer conductor	Copper, Tin plated	Braid, 78 %	12.55 mm
Jacket	PE (Polyethylene)	RAL 9005 - bk	14.99 mm +/- 0.25

Print: HUBER+SUHNER SPUMA 600 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	78 pF/m
Velocity of signal propagation	85 %
Signal delay	3.9 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 90 dB (up to 6 GHz)
Max. operating voltage	≤ 2 kV _{rms} (at sea level)
Test voltage	4 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	20 kg/100 m
Min. bending radius	static 38 mm
	repeated (for ≤ 50 bendings) 152 mm

Environmental Data

Temperature range	-40 °C... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen test	IEC 60754
2011/95/EC (RoHS)	compliant

Additional Information

Ordering Information

Order as	SPUMA_600
----------	-----------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	X29 12 mm / 50 Ohm
-------------	--------------------

Coaxial Cable SPUMA_600

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.0786

b = 0.008

f_{max} = 6

P at 1GHz = 930

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.3	0.05	0.014	1698
0.6	0.07	0.020	1201
0.9	0.08	0.025	980
1.2	0.1	0.029	849
1.5	0.11	0.033	759
1.8	0.12	0.037	693
2.1	0.13	0.040	642
2.4	0.14	0.043	600
2.7	0.15	0.046	566
3.0	0.16	0.049	537
3.3	0.17	0.052	512
3.6	0.18	0.054	490
3.9	0.19	0.057	471
4.2	0.19	0.059	454
4.5	0.2	0.062	438
4.8	0.21	0.064	424
5.1	0.22	0.067	412
5.4	0.23	0.069	400
5.7	0.23	0.071	390
6.0	0.24	0.073	380