

LIGHT ENGINE 560 x 10mm 550lm

Issue Date	Jul - 2017
Issued by	Wilbur C.

Applications

- Troffers
- Battens
- Panels
- Linear Luminaire

Characteristics

- Module Efficacy – up to 138lm/W
- L70 > 50.000 hours
- CRI > 80 (Typ.85)
- 03 SDCM
- CCTs 3.000K / 4.000K / 5.000K
- 05 years warranty



Zhaga

DRIVE CURRENTS

Parameter	Nominal	Max
Light Engine Linear 175	700 mA	700 mA

MODULE TEMPERATURES

Parameter	Nominal	Max
Tc (case temperature at Tc point)	60 °C	85 °C


PRODUCT PART NUMBER

80048400100	80048500100	80048600100
3.000 K	4.000 K	5.000 K


TECHNICAL INFORMATION

CCT	LED Driver Current (mA)	# LEDs	Luminous Flux (lm)*	Forward Voltage (V)	LED Forward Current (mA)	TC (°C)	Power (W)	Efficacy (lm/W)*
3.000 K	350	12	293	5,6	58	75	2,0	148
3.000 K	500	12	399	5,8	83	75	2,9	139
3.000 K	700	12	536	5,9	117	75	4,1	130
4.000 K	350	12	299	5,6	58	75	2,0	151
4.000 K	500	12	408	5,8	83	75	2,9	142
4.000 K	700	12	547	5,9	117	75	4,1	133
5.000 K	350	12	311	5,6	58	75	2,0	158
5.000 K	500	12	425	5,8	83	75	2,9	148
5.000 K	700	12	570	5,9	117	75	4,1	138

Luminous Flux (lm) x Forward Current (mA) (TC 60°C)



Forward Voltage (V) x Forward Current (mA) (TC 60°C)




LED TYPE

Manufacturer: Nichia Corporation

LED Series: TART

MECHANICAL DRAWING



Unit: mm

WIRING

Specification item	Value	Unit	Condition
Input wire cross- section	0.25...0.75 18...24	mm ² AWG	Solid wire
Input wire strip length	7.5...8.5	mm	Solid wire
Input wire cross-section	0.33...0.5 20...22	mm ² AWG	Stranded wire
Input wire strip length	7.5...8.5	mm	Stranded wire

DRIVER FOR 08 LIGHT ENGINES: LED DRIVER 40W 220-240VAC ([EIP040C0700L1](#))

DRIVER FOR 12 LIGHT ENGINES: LED DRIVER 60W 220-240VAC ([EIP060C0700L2](#))