

ROUND FIT DLC PREMIUM

HIGHER EFFICACY FOR INTERNAL APPLICATIONS

AUDAX
ELECTRONICS

LIGHT ENGINE Ø120mm 2.000lm

Issue Date	Jul - 2017
Issued by	Wilbur C.

Application

- Downlights

Characteristics

- Module Efficacy – up to 139 lm/W
- L70 > 50.000 hours
- CRI > 80 (Typ.85)
- 03 SDCM
- CCTs 3.000K / 4.000K / 5.000K
- 05 years warranty



DRIVE CURRENTS

Parameter	Nominal	Max
Light Engine Round Fit DLC Premium	700 mA	700 mA

MODULE TEMPERATURES

Parameter	Nominal	Max
Tc (case temperature at Tc point)	60 °C	85 °C

PRODUCT PART NUMBER

80084100100	80084200100	80084300100
3.000 K	4.000 K	5.000 K


TECHNICAL INFORMATION

CCT	LED Driver Current (mA)	# LEDs	Luminous Flux (lm)*	Forward Voltage (V)	LED Forward Current (mA)	TC (°C)	Power (W)	Efficacy (lm/W)*
3.000 K	700	28	2.507	22,8	50	60	16,0	157
4.000 K	700	28	2.544	22,8	71	60	16,0	159
5.000 K	700	28	2.630	22,8	100	60	16,0	164

LED TYPE

Manufacturer: Nichia Corporation

LED Series: 757



Unit: mm

WIRING

Specification item	Value	Unit	Condition
Input wire cross- section	0.25...0.75 18...24	mm ² AWG	Solid wire
Input wire strip length	7.5...8.5	mm	Solid wire
Input wire cross-section	0.33...0.5 20...22	mm ² AWG	Stranded wire
Input wire strip length	7.5...8.5	mm	Stranded wire

DRIVER FOR 1 LIGHT ENGINES: LED DRIVER 21W 220-240VAC (EIP021C0700L2)

