

LIGHT ENGINE 280 x 20mm 1.100lm

Issue Date	Jul - 2017
Issued by	Wilbur C.

Applications

- Troffers
- Battens
- Panels
- Linear Luminaire

Characteristics

- Module Efficacy – up to 138lm/W
- L70 > 50.000 hours
- CRI > 80 (Typ.85)
- 03 SDCM
- CCTs 3.000K / 4.000K / 5.000K
- 05 years warranty



Zhaga

DRIVE CURRENTS

Parameter	Nominal	Max
Light Engine Linear 175	700 mA	700 mA

MODULE TEMPERATURES

Parameter	Nominal	Max
Tc (case temperature at Tc point)	60 °C	85 °C


PRODUCT PART NUMBER

80085900100	80086000100	80086100100
3.000 K	4.000 K	5.000 K


TECHNICAL INFORMATION

CCT	LED Driver Current (mA)	# LEDs	Luminous Flux (lm)*	Forward Voltage (V)	LED Forward Current (mA)	TC (°C)	Power (W)	Efficacy (lm/W)*
3.000 K	350	24	586	11,3	58	75	4,0	148
3.000 K	500	24	799	11,5	83	75	5,8	139
3.000 K	700	24	1.071	11,8	117	75	8,2	130
4.000 K	350	24	598	11,3	58	75	4,0	151
4.000 K	500	24	816	11,5	83	75	5,8	142
4.000 K	700	24	1.094	11,8	117	75	8,2	133
5.000 K	350	24	623	11,3	58	75	4,0	158
5.000 K	500	24	850	11,5	83	75	5,8	148
5.000 K	700	24	1.139	11,8	117	75	8,2	138

Luminous Flux (lm) x Forward Current (mA) (TC 60°C)



Forward Voltage (V) x Forward Current (mA) (TC 60°C)




LED TYPE

Manufacturer: Nichia Corporation

LED Series: TART

MECHANICAL DRAWING




Unit: mm

WIRING

Specification item	Value	Unit	Condition
Input wire cross- section	0.25...0.75 18...24	mm ² AWG	Solid wire
Input wire strip length	7.5...8.5	mm	Solid wire
Input wire cross-section	0.33...0.5 20...22	mm ² AWG	Stranded wire
Input wire strip length	7.5...8.5	mm	Stranded wire

DRIVER FOR 2 LIGHT ENGINES: LED DRIVER 21W 220-240VAC (EIP021C0700L2)



DRIVER FOR 4 LIGHT ENGINES: LED DRIVER 40W 220-240VAC (EIP040C0700L1)

