

Technical Data Sheet

High Power Infrared LED

IR-S06-P120/L741-P03/TR



Features

- Small package with high efficiency
- Peak wavelength $\lambda_p = 940$ nm
- Soldering methods: SMT
- Pb free
- Compliance with EU REACH
- Compliance Halogen Free (Br < 900ppm, Cl < 900ppm, Br+Cl < 1500ppm)
- The product itself will remain within RoHS compliant version.

Description

- IR-S06-P120/L741-P03/TR series is an infrared emitting diode in miniature SMD package which is molded in a water clear epoxy with flat top view lens.
- The device is spectrally matched with silicon photo diode, phototransistor.

Applications

- CCD Camera
- Infrared applied system

Device Selection Guide

LED Part No.	Chip Material	Lens Color
IR-S06-P120/L741-P03/TR	GaAlAs	Water clear

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Rating	Unit
Continuous Forward Current	I_F	1000	mA
Reverse Voltage	V_R	5	V
Operating Temperature	T_{opr}	-40 ~ +100	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-40 ~ +100	$^{\circ}\text{C}$
Junction temperature	T_j	145	$^{\circ}\text{C}$
Power Dissipation @ $I_F=700\text{mA}$	P_d	3	W

Notes:

- We suggest that customer should add the heat sink with IR-S06-P120/L741-P03/TR to exclude the heat.

Electro-Optical Characteristics ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Total Radiated Power	P_o	--	355	--	mW	$I_F=350\text{ mA}$
		--	700	--		$I_F=700\text{ mA}$
		--	1000	--		$I_F=1\text{ A}$
Radiant Intensity	I_E	--	120	--	mW/sr	$I_F=350\text{ mA}$
		--	250	--		$I_F=700\text{ mA}$
		--	360	--		$I_F=1\text{ A}$
Peak Wavelength	λ_P	--	940	--	nm	$I_F=350\text{ mA}$
Spectral Bandwidth	$\Delta\lambda$	--	25	--	nm	$I_F=350\text{ mA}$
Forward Voltage	V_F	--	2.6	--	V	$I_F=350\text{ mA}$
		--	2.8	--		$I_F=700\text{ mA}$
		--	2.9	--		$I_F=1\text{ A}$
Reverse Current	I_R	--	--	10	μA	$V_R=5\text{ V}$
View Angle	$2\theta_{1/2}$	--	120	--	deg	$I_F=20\text{ mA}$

Typical Electro-Optical Characteristics Curves

Fig.1

Forward Current vs. Forward Voltage




Fig.2

Forward Current vs. Intensity




Fig.3

Forward Current vs. Total Power






Fig.4





Relative Radiant Intensity vs. Angular Displacement



Package Dimension




Polarity



1. Dimensions are in millimeters.
2. Tolerances unless mentioned are $\pm 0.1\text{mm}$.
3. Do not handle the device by the lens. Incorrect force applied to the lens may lead to the failure of devices.

Package Dimensions




Note:

1. Dimensions are in millimeters
2. The tolerances unless mentioned is $\pm 0.1\text{mm}$

Carrier Tape Dimensions:


Loaded quantity 800 pcs per reel.



Note:

1. Dimensions are in millimeters
2. The tolerances unless mentioned is $\pm 0.1\text{mm}$

Moisture Resistant Packaging



Moisture Resistant Packing Materials

Label Form Specification

RoHS  EVERLIGHT	
CPN : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX	
P/N : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX	
LOT NO : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX	
QTY :	HUE : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX
CAT :	REF : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX
REFERENCE : XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX	



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number
- X: Month
- Reference: Identify Label Number

EVERLIGHT ELECTRONICS CO., LTD.

Office: No 6-8, Zhonghua Rd., Shulin Dist.,

Tel: 886-2-2685-6688

Fax: 886-2-2685-6897

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.